

WHITE

MOLD ARMOR®

100% SILICONE

MOLD FREE

CAULK & SEALANT

NO MOLD, MILDEW
OR SCRUBBING*



**20 YEAR MOLD-FREE
MONEY BACK GUARANTEE**

**Shower, Tub,
Kitchen & Countertop**

**Waterproof in
30 minutes**

**Won't yellow,
shrink or crack**

NET CONTENTS: 5.5 FL. OZ. (162.6 mL)

READY TO USE!

**Durable, mold and mildew-free
silicone. Flexible, crack-proof
formula with excellent adhesion.**

FOR SURFACES SUCH AS:

- Glass
- Wood
- Aluminum
- Granite
- Ceramic
- Fiberglass
- Marble
- Metal
- Painted Surfaces

Test all surfaces before use. This product is not paintable. The paint film will not stretch with the sealant.

DIRECTIONS

1. Remove any existing caulk, dirt, grease or soap residue. If mold is present, use a mold and mildew cleaner such as Mold Armor Mold & Mildew Killer & Quick Stain Remover to kill any mold on the surface. Once dry, surface is ready for application.
2. Cut the tip of the nozzle to the required bead size.
3. Rest the nozzle on the joint and apply a bead into the gap. Immediately smooth with a gloved finger or tool.
4. Clean up immediately (before drying) with a solvent such as acetone.
5. Allow 30 minutes before water exposure. Product is generally fully cured in 24 hours, depending on size of bead, temperature and humidity.

Do not get on skin or in eyes. Do not ingest. Wear gloves and safety glasses. In an emergency, call the Poison Control Center at 1-800-222-1222 or get immediate medical attention.

Do not store at elevated temperatures.

Product Category: Chemically Curing Sealant or Caulking Compound

Max VOC: 3 %

* Cured caulk & sealant is mildew resistant. Regular cleaning of cured sealant is required, as soap and other residue can cause secondary mold and mildew growth.

QUESTIONS? COMMENTS?


CALL 844-969-1373

www.moldarmor.com

©2020 W.M. Barr, Inc.

Sold by:
W.M. Barr, Inc.
Memphis, TN 38113

Made in U.S.A.



FG573 / Q0635